

KEEP THE SAME WALL, UPGRADE EVERYTHING ELSE

Unlike competitive products that leave ghostly reminders of past installations, Vive™ controls fit the existing vacancies left by old thermostats and are easy to install. The lineup includes industry-leading features like:

- ☒ 5-year warranty coverage
- ☒ Universal system compatibility
- ☒ Extra-large, easy-to-read backlit LED display
- ☒ Tethered and wireless installation options
- ☒ Tactile button or touchscreen operation
- ☒ Residential and commercial flexibility
- ☒ Universal base plate with color-coded terminals



ENHANCE CUSTOMER RELATIONSHIPS

All Vive™ controls have a removable badge that can be easily replaced with one featuring customized business information. Large inventory purchases are NOT required to take advantage of our private label program. It's easy and free regardless of how many units are purchased!



IMPROVED COMFORT ON ANY BUDGET

Vive™ offers an easy and affordable solution to enhance comfort by controlling home and office temperatures remotely. By adding up to four remote sensors to the wireless thermostat, temperatures can be set one room at a time or by averaging each space. Plus, installation is simple and very cost effective, saving time and money.



WIRELESS
CONVERSION KIT



INDOOR REMOTE
SENSOR



OUTDOOR REMOTE
SENSOR

LIVE COMFORTABLY

With a tablet-style design and intuitive functionality, Vive™ products respond to every phase of life with corresponding comfort and style. Our cutting edge temperature management is wireless capable, easy to program and user-friendly, and it communicates with almost any HVAC system. Advanced technology and the large, blue LED display offer timeless appeal with contemporary flair. Experience the exclusive controls that bring maximum performance, efficiency and comfort into the home or commercial setting.



900 SERIES



800 SERIES



700 SERIES



600 SERIES

VIVE™

1-800-776-1635 | VIVECOMFORT.COM

VIVE™

COMFORT

COMPLETE LINEUP



THE MOST COMPLETE LINEUP
OF HIGH-PERFORMANCE
THERMOSTATS

VIVE™

COMFORT



WIRELESS

WIRELESS

PROGRAMMING OPTIONS

- 7D** 7 Day **2P** Commercial 2 Time Periods (occupied/unoccupied)
- 5/1/1** M-F, SAT & SUN **NP** Non-Programmable

	600 SERIES					700 SERIES							800 SERIES			900 SERIES				
	TP-N-601	TP-P-605	TP-N-621	TP-N-631	TP-N-631W	TP-N-701	TP-P-705	TP-N-721	TP-P-725	TP-N-751	TP-S-755	TP-S-755H	TP-S-755R	TP-N-801	TP-N-851	TP-S-855C	TP-S-905	TP-S-955C	TP-S-955WH	TP-Z-955W
	NP	5/1/1	NP	NP	NP	NP	5/1/1	NP	5/1/1	NP	5/1/1 NP	5/1/1 NP	5/1/1 NP	NP	NP	7D 5/1/1 NP 2P	7D 5/1/1 NP	7D 5/1/1 NP 2P	7D 5/1/1 NP	7D 5/1/1 NP
HEAT STAGES	1	1	2	2*	2*	1	1	2	2	3**	3**	3**	3**	1	3**	3**	1	3**	3**	3**
COOL STAGES	1	1	1	1	1	1	1	1	1	2	2	2	2	1	2	2	1	2	2	2
GAS, ELECTRIC OR OIL	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
HEAT PUMP	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
AUXILIARY HEAT			•	•	•			•	•	•	•	•	•			•			•	•
EMERGENCY HEAT			•					•	•	•	•	•	•			•			•	•
TWO-SPEED FAN (PTAC)				•	•															
CONVENTIONAL HEAT/COOL	•	•		•	•	•	•			•	•	•	•	•	•	•	•	•	•	•
MILLIVOLT	•	•				•	•			•	•	•	•	•	•	•	•	•	•	•
BATTERY POWERED	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
24V POWER (HARDWARE)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
DUAL FUEL COMPATIBLE			S					S	S	S	S	S	H		S	S		S	H	H
DISPLAY SIZE (SQUARE INCHES)	2"	2"	2"	2"	2"	4"	4"	4"	4"	6"	6"	6"	6"	8"	8"	8"	13"	13"	13"	13"
AUTO CHANGEOVER														•	•	•	•	•	•	•
FILTER CHANGE REMINDER		•					•	•	•	•	•	•	•	•	•	•	•	•	•	•
ROOM TEMPERATURE CALIBRATION	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
MINIMUM COMPRESSOR RUN TIME		•					•	•	•	•	•	•	•	•	•	•	•	•	•	•
COMPRESSOR SHORT CYCLE DELAY	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
ADJUSTABLE HEATING TEMPERATURE SWING	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
ADJUSTABLE COOLING TEMPERATURE SWING	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
PROGRAMMABLE FAN											•	•	•			•	•	•	•	•
KEYPAD LOCKOUT														•	•	•	•	•	•	•
LIGHT COMMERCIAL COMPATIBLE																•	•	•	•	•
ADJUSTABLE SETPOINT LIMITS				•	•						•	•	•	•	•	•	•	•	•	•
AVERAGING AND REMOTE SENSOR CAPABLE													•						•	•
HUMIDITY CONTROL												•							•	•
TOUCHSCREEN																	•	•	•	•
HUMIDITY PAD, UV BULB AND IAQ CELL REMINDER														•	•	•	•	•	•	•
CONTINUOUS ON BACKLIGHT OPTION															•	•	•	•	•	•
CONTRACTOR PHONE NUMBER ON SCREEN														•	•	•	•	•	•	•
5-YEAR WARRANTY	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
TERMINALS	Rh W Rc G C B Y O	Rh W Rc G C B Y O	R E C G Y B W2 O	R GL C GH Y O/B W	R GL C GH Y O/B W	Rh W Rc G C B Y O	Rh W Rc G C B Y O	R E C G Y B W2 O	R E C G Y B W2 O	Rh W/E Rc W2 C G Y B Y2 O	Rh W/E Rc W2 C G Y B Y2 O	Rh W2 Rc G C B Y O Y2 H W/E D	Rh W2 Rc G C B Y O Y2 S1 W/E S2	Rh W Rc G C B Y O	Rh W/E Rc W2 C G Y B Y2 O	Rh W/E Rc W2 C G Y B Y2 O	Rh W Rc G C B Y O	Rh W/E Rc W2 C G Y B Y2 O	Rh W2 Rc G C B Y O Y2 H W/E D	Rh W/E Rc W2 C G Y B Y2 O

*2 heat stages for heat pump or 1 heat stage for conventional. **3 heat stages for heat pump or 2 heat stages for conventional. H= Dual fuel hardware balance point. Requires Outdoor Temperature Sensor accessory TP-R0S-250W or TP-R0S-250S. S= Dual fuel software setting.

ACCESSORIES

- Tethered Outdoor Temp Sensor (TP-R0S-250S)
- Wireless Outdoor Temp Sensor (TP-Z-R0SW)
- Tethered Indoor Temp Sensor (TP-RIS-2515)
- Wireless Indoor Temp Sensor (TP-Z-RISW)
- Wireless Repeater (TP-W150W)
- Wireless Conversion Kit (TP-WCTO)
- Universal Wall Plate (TP-119)
- Weatherproof Enclosure (TP-E219)
- Thermostat Guard (TP-G150)